

# The Right Answer for Commercial Contractors

Ramset's fully automatic RA27 powder-actuated tool, lowering downtime and fatigue on commercial jobsites. The RA27 stands up to toughest use for interior and exterior applications.

Power adjust dial enables user to dial down power for ideal pin embedment

More power, load for load, provides flexibility in a wide range of applications

Patented RRC (Residue Release Channel) allows tool to work

longer between cleanings



# **Common Applications**







TRACK-TO-STEEL



**EXTERIOR CLADDING CLIPS** 



**DEEP LEG** TRACK



**ELECTRICAL**/ UNISTRUT



CHANNEL

Lower pushdown force reduces fatigue; easier to use overhead

reduces downtime

Long-lasting piston

Durable magazine providing up to 30% longer lifespan

Collar requires only 1/4 turn for quicker cleaning

## GREEN RED **POWDERLOAD IDENTIFICATION**

Lower Power → Higher Power

## **RA27 Tool Specifications:**

- Part Number: RA27
- Weight: 5.3 lbs
- Maximum pin length without washer: 11/2"
- Maximum pin length with washer: 2"
- 3-year warranty
- For use with .27 caliber loads (green, yellow, red)

## **RA27MAG Magazine Specifications:**

- Part Number: RA27Mag
- Weight: 1.3 lbs
- Maximum pin length: 1¼"

## **RA27 Tool Includes:**

- Safety glasses
- Spall guard
- Two cleaning brushes
- Operators manual

Magazine and tool sold separately

# TRUE EMBEDMENT PINS

The Ramset .157 True Embedment Pin is sized to provide you with True Embedment depths in track up to 14 gauge. Sized approximately 1/16" longer than nominal length to provide a True Embedment. 100 per box.



PART	PIN LENGTH		EMBEDMENT LENGTH		MASTER CARTON
NUMBER	IN.	(MM)	IN.	(MM)	QUANTITY
TE12	9/16	(13.8)	1/2	(12.7)	5000
TE34	13/16	(20.6)	3/4	(19.1)	5000
TE100	1-1/16	(27)	1	(25.4)	5000
TE114	1-5/16	(33.3)	1-1/4	(31.8)	1000

Shank diameter = .157 Head diameter = .320

# TRUE EMBEDMENT COLLATED PINS

The Ramset .157 True Embedment Pin is sized to provide you with True Embedment depths in track up to 14 gauge. Sized approximately 1/16" longer than nominal length to provide a True Embedment. 1000 per box. Collated for use with the RA27MAG.



PART	PIN LENGTH		EMBEDMENT LENGTH		MASTER CARTON
NUMBER	IN.	(MM)	IN.	(MM)	QUANTITY
TE12X	9/16	(13.8)	1/2	(12.7)	5000
TE34X	13/16	(20.6)	3/4	(19.1)	5000
TE100X	1-1/16	(27)	1	(25.4)	5000
TE114X	1-5/16	(33.3)	1-1/4	(31.8)	5000

Shank diameter = .157 Head diameter = .320

## **POWERPOINT PINS**

Premium pin used for fastening into harder steel and concrete. Premium steel and hard concrete pin. 100 per box.



PART	SHANK	LENGTH	MASTER CARTON	
NUMBER	IN.	(MM)	QUANTITY	
SP12	1/2	(12.7)	5000	
SP58	5/8	(15.9)	5000	
SP34	3/4	(19.1)	5000	
SP114*	1-1/4	(31.8)	1000	
SP178*	1-7/8	(47.6)	1000	
M100BB**	100BB** 1		4000	

Shank diameter = .150 \* Head diameter = .150/.180 \*\* Shank diameter = .125/.150 with 1/2" washer Head diameter = .300

### **PLATED PINS**

Designed for use in concrete and structural steel applications. 100 per box.



PART	SHANK L		MASTER CARTON QUANTITY		
NUMBER	IN.	(MM)			
1503K	1/2 Knurled	(12.7)	5000		
1506	3/4	(19.1)	5000		
1508	1	(25.4)	5000		
1510	1-1/4	(31.8)	1000		
1512	1-1/2	(38.1)	1000		
Shank diameter = .145 Head diameter = .300					

## **WASHERED PINS**

Washer increases bearing surface against the material to be fastened. Plated pin pre-assembled with 7/8" diameter washer.



1	PART	SHANK L	ENGTH	MASTER CARTON	
	NUMBER	IN.	(MM)	QUANTITY	
	1506SD	3/4	(19.1)	1000	
	1508SD	1	(25.4)	1000	
	1510SD	1-1/4	(31.8)	1000	
	1512SD	1-1/2	(38.1)	1000	
ĺ	1514SD	2	(50.8)	1000	
	Shank diameter = .145 Head diameter = .300 16 gage metal washer				

#### POWERPOINT TOP HAT PIN

Used for general purpose fastening to steel. Plated pin with top hat. 100 per box.



PART	SHANK	LENGTH	MASTER CARTON		
NUMBER	IN.	(MM)	QUANTITY		
SP58TH	5/8"	15.9	5000		
Shank diameter = .150 Head diameter = .300					

RAMSET .27 CALIBER LOADS					
PART NUMBER	POWER LEVEL	COLOR	PACKAGING	MASTER CARTON QUANTITY	
3RS27	3	Green	All 10 shot strip 10 strips/box	10,000	
4RS27	4	Yellow	All 10 shot strip 10 strips/box	10,000	
5RS27	5	Red	All 10 shot strip 10 strips/box	10,000	

## ONE HOLE CONDUIT STRAP

Used to attach EMT conduit or armored cable to concrete.

PowerPoint fastener pre-assembled to a 16 gage conduit strap. 100 per box.



PART Number	DESCRIPTION	MASTER CARTON QUANTITY
38HSSS10*	3/8" Hole strap with w/1 premium pin	500
12HSSS10	1/2" Hole strap with w/1 premium pin	500
34HSSS10 3/4" Hole strap with w/1 premium pin		500
Shank diameter = .125/.150	Head diameter = .300 *38HSMP034 = 18 gage, 2	200 per jar

THREADED ROD HANGER

For suspended ceilings, piping, and other items using 1/4" or 3/8" threaded rod. PowerPoint fastener pre-assembled to a 16 gage threaded rod hanger. 100 per box.



PART Number	DESCRIPTION	MASTER CARTON QUANTITY
14TRHSS10	1/4" Rod hanger w/1" premium pin	500
38TRHSS10	3/8" Rod hanger w/1" premium pin	500
Shank diameter = .125/.150	Head diameter = .300	

**RA27** 

ramset.com

